



## SAFETY DATA SHEET

### 1001 NO VAC - SPRING RAIN

According to Regulation (EC) No 1907/2006

#### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME 1001 NO VAC - SPRING RAIN

INTERNAL ID EU F0043

APPLICATION Carpet freshener.

SUPPLIER WD-40 Company Limited  
PO Box 440  
Kiln Farm  
Milton Keynes  
MK11 3LF  
Tel: 01908 555400  
Fax: 01908 266900  
info@wd40.co.uk

EMERGENCY TELEPHONE 00 44 1908 555 400 (08.00 - 16.30)

#### 2 HAZARDS IDENTIFICATION

Extremely flammable.

CLASSIFICATION F+;R12.

##### PHYSICAL AND CHEMICAL HAZARDS

Aerosol containers can explode when heated, due to excessive pressure build-up. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited.

##### HUMAN HEALTH

See section 11 for additional information on health hazards.

#### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
BUTANE	203-448-7	106-97-8	1-5%	F+;R12
ISOBUTANE	200-857-2	75-28-5	1-5%	F+;R12
PROPAN-2-OL	200-661-7	67-63-0	1-5%	F;R11 Xi;R36 R67
PROPANE	200-827-9	74-98-6	1-5%	F+;R12

The Full Text for all R-Phrases are Displayed in Section 16

#### 4 FIRST-AID MEASURES

##### INHALATION

Vapours may irritate throat and respiratory system and cause headache, dizziness and dullness. Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention.

##### INGESTION

Not expected to be a hazard under normal use, however, if swallowed: DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Immediately rinse mouth and drink plenty of water (200-300 ml). Get medical attention.

##### SKIN CONTACT

Prolonged and frequent contact may cause redness and irritation. Remove contaminated clothing immediately and wash skin with soap and water.

##### EYE CONTACT

Spray and vapour in the eyes may cause irritation and smarting. Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

#### 5 FIRE-FIGHTING MEASURES

# 1001 NO VAC - SPRING RAIN

**EXTINGUISHING MEDIA**

Use: Foam. Water spray, fog or mist. Dry chemicals, sand, dolomite etc.

**SPECIAL FIRE FIGHTING PROCEDURES**

Containers close to fire should be removed or cooled with water. Avoid water in straight hose stream; will scatter and spread fire.

**UNUSUAL FIRE & EXPLOSION HAZARDS**

Aerosol cans may explode in a fire.

**SPECIFIC HAZARDS**

Fire or high temperatures create: Carbon monoxide (CO). Carbon dioxide (CO2).

**PROTECTIVE MEASURES IN FIRE**

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

**6 ACCIDENTAL RELEASE MEASURES**

**PERSONAL PRECAUTIONS**

Wear protective clothing as described in Section 8 of this safety data sheet.

**SPILL CLEAN UP METHODS**

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb with inert, damp, non-combustible material, then flush area with water.

**7 HANDLING AND STORAGE**

**USAGE PRECAUTIONS**

Read and follow manufacturer's recommendations. Keep away from heat, sparks and open flame. Avoid inhalation of vapours/spray and contact with skin and eyes.

**STORAGE PRECAUTIONS**

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

**8 EXPOSURE CONTROLS/PERSONAL PROTECTION**

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
BUTANE	WEL	600 ppm	1450 mg/m3	750 ppm	1810 mg/m3	
PROPAN-2-OL	WEL	400 ppm	999 mg/m3	500 ppm	1250 mg/m3	

WEL = Workplace Exposure Limit.

**PROTECTIVE EQUIPMENT**



**ENGINEERING MEASURES**

Provide adequate ventilation.

**HAND PROTECTION**

For prolonged or repeated skin contact use suitable protective gloves. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

**EYE PROTECTION**

Wear approved chemical safety goggles where eye exposure is reasonably probable.

**HYGIENE MEASURES**

DO NOT SMOKE IN WORK AREA! Promptly remove any clothing that becomes contaminated. Wash promptly if skin becomes contaminated. When using do not eat, drink or smoke.

**9 PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE	Aerosol Liquid
COLOUR	Colourless
ODOUR	Perfume scent

**10 STABILITY AND REACTIVITY**

# 1001 NO VAC - SPRING RAIN

**STABILITY**

Stable under normal temperature conditions and recommended use.

**CONDITIONS TO AVOID**

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

**MATERIALS TO AVOID**

Strong oxidising substances.

**HAZARDOUS DECOMPOSITION PRODUCTS**

During fire, toxic gases (CO, CO2) are formed.

## 11 TOXICOLOGICAL INFORMATION

**INHALATION**

Vapours may irritate throat and respiratory system and cause headache, dizziness and dullness.

**INGESTION**

No harmful effects expected in amounts likely to be ingested by accident.

**SKIN CONTACT**

Prolonged contact may cause redness and irritation.

**EYE CONTACT**

May cause temporary eye irritation.

## 12 ECOLOGICAL INFORMATION

**ECOTOXICITY**

The product is not expected to be hazardous to the environment.

## 13 DISPOSAL CONSIDERATIONS

**DISPOSAL METHODS**

Dispose of waste and residues in accordance with local authority requirements. Make sure containers are empty before discarding (explosion risk). Recover and reclaim or recycle, if practical.

## 14 TRANSPORT INFORMATION



UK ROAD CLASS	2.1	UK ROAD PACK GR.	#
PROPER SHIPPING NAME	AEROSOLS	ADR CLASS	Class 2: Gases
UN NO. ROAD	1950	ADR LABEL NO.	2.1
ADR CLASS NO.	2.1	RID CLASS NO.	2.1
ADR PACK GROUP	#	UN NO. SEA	1950
CEFIC TEC(R) NO.	20G5F	IMDG PACK GR.	#
RID PACK GROUP	#	MARINE POLLUTANT	No.
IMDG CLASS	2.1	AIR CLASS	2.1
EMS	F-D, S-U		
UN NO. AIR	1950		
AIR PACK GR.	#		

## 15 REGULATORY INFORMATION

**LABELLING**



Extremely Flammable

**1001 NO VAC - SPRING RAIN**

## RISK PHRASES

R12 Extremely flammable.

## SAFETY PHRASES

S2 Keep out of the reach of children

S16 Keep away from sources of ignition - No smoking.

S23 Do not breathe vapour/spray.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S35 This material and its container must be disposed of in a safe way.

S51 Use only in well-ventilated areas.

A1 Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

A2 Do not spray on a naked flame or any incandescent material.

## EU DIRECTIVES

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

## STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

## APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply.

## GUIDANCE NOTES

Workplace Exposure Limits EH40.

**16 OTHER INFORMATION**

## REVISION COMMENTS

Safety Phrases amended.

REVISION DATE 11-2008

REV. NO./REPL. SDS GENERATED 4 / 10-2008

SDS NO. 10047

## RISK PHRASES IN FULL

R11 Highly flammable.

R12 Extremely flammable.

R36 Irritating to eyes.

R67 Vapours may cause drowsiness and dizziness.